
REAR FACE OF CYL. BLOCK
REVERSE GEAR
LUBE OIL FILTER
VIEW A
DIA-2 HOLES
5'36" 'M' GEAR
5'35" 'MH' GEAR
7.41
43.29 'M' GEAR
6.59
43.43 'MH' GEAR
OPTIONAL-RESILIENT TYPE ENGINE MOUNTS INSTALLATION ANGLE
NEUTRAL POSITION CAN BE ROTATED CLOCKWISE AS MUCH AS 90°
NEUTRAL
FORWARD
REVERSE
30°
30°
TO PROP SHAFT FL'GE.
TO ℄ OF PROP SHAFT
REVERSE GEAR SELECTOR LEVER (FULL SIZE)
COMPANION FLANGE CUSTOMER TO BORE 4.00 DIA. (MAX MH GEAR)
RAW WATER OUTLET ABOVE PROP SHAFT ℄
TO PROP SHAFT FL'GE
ENGINE
RAW WATER INLET 24 ABOVE PROP SHAFT ℄
FUEL COOLER
SKETCH OF RAW WATER OPTIONAL PIPING CAN NOT BE USED WITH FLANGE MOUNTED AIR COMPRESSOR
EXHAUST ELBOW-WATER COOLED (OPTIONAL) (BOTH SIDES)
WATER INLET DIA
COMPANION FLANGE CUSTOMER TO BORE DIA. MAX (M GEAR) SHIPPED LOOSE)
OIL LEVEL (REVERSE GEAR) (7082-7300 SHOWN 7082-7300 OPPOSITE)
REVERSE GEAR OIL FILLER
EXHAUST OUTLET (FULL SIZE)
-18 UNC THD-DEEP HOLES
DIA.
AIR COMPRESSOR OUTLET (FULL SIZE)
EXHAUST OUTLET-SEE DETAIL
ADAPTOR & TURBINE HSG INSULATION BLANKETS (SHIPPED LOOSE)
LIFTER EYE
RAW WATER OUTLET 2 DIA
HEIGHT
TACHOMETER DRIVE SAE SIZE
LUBE OIL LEVEL GAGE FOR 7082-3300
LUBE OIL LEVEL GAGE FITS 7082-7300
FUEL RETURN INTERNAL NPTF 25 LG FLEX HOSE
RAW WATER INLET OD
BELT GROOVE-WIDE 36° INCLUDED ANGLE
FUEL COOLER
EXHAUST MANIFOLD
GENERATOR
STARTER
BATTERY TERMINALS
REVERSE GEAR OIL FILTER
DIA.
DIA-4 HOLES
REAR FACE OF BLOCK
'M' GEAR
REVERSE GEAR OIL STRAINER (7082-3300 SHOWN (7082-7300 OPPOSITE)
REVERSE GEAR OIL PRESS. CONN. INTERNAL NPTF THD FLEXIBLE HOSE
'M' GEAR' FLANGE DIA.-6 HOLES EQUALLY SPACED ON 8.00 DIA. B.C.
'MH GEAR' FLANGE DIA.8 HOLES EQUALLY SPACED ON 7.50 DIA. B.C.
7082-7300
7082-3300
24 CENTERS
REVERSE GEAR RATIOS
'MH GEARS'
'M GEARS'
REVERSE GEAR
OIL DRAIN
REAR OF BLOCK
DIA
SUMP PUMP ATTACHING HOSE SHIPPED LOOSE.
8V-71TI