


## 3126B MARINE ENGINE – 336 kW (450 bhp)



### DIMENSIONS



### RATING DEFINITIONS AND CONDITIONS

**E RATING** – Planing hull vessels such as pleasure craft, harbor patrol, harbor master, and some fishing and pilot boats.

**RATINGS** are based on SAE J1228/ISO8665 standard conditions of 100 kPa (29.61 in Hg), 25° C (77° F), and 30% relative humidity. These ratings also apply at ISO3046/1, DIN6271/3, and BS5514 conditions of 100 kPa (29.61 in Hg), 27° C (81° F), and 60% relative humidity. Ratings are valid for air cleaner inlet temperatures up to and including 50° C (122° F) and for sea water temperatures up to and including 42° C (108° F) at sea level.

**FUEL RATES** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal). Fuel consumption shown with all oil, fuel, and water pumps, engine driven. For a “without pumps” condition, deduct approximately 0.5% for each pump not engine driven.

Additional ratings may be available for specific customer requirements. Consult your Caterpillar representative for additional information.