



Specifications

	<u>Metric</u>
Power Ratings	
Maximum	295 bhp
Rated RPM	2600
Fuel Consumption at rated rpm	16.1 GPH
Light Duty	295 bhp
Rated RPM	2600
Fuel Consumption at rated rpm	16.1 GPH
Continuous Duty	255 bhp
Rated RPM	2300
Fuel Consumption at rated rpm	13.4 GPH
Four Stroke Cycle, Naturally Aspirated, V8 Diesel Engine.	
Bore and Stroke	5½ x 4¾ in. 140 x 121 mm
Displacement	903 cu. in. 14.8 L
Oil Pan Capacity	5 U.S. gals. 19 L
Net Weight, Dry†	2800 lbs. 1 270 kg
Installation Diagram Number	218133

†With selected accessories and Capitol 4HE-10200 marine gear.

Available Equipment

- Accessory Drive:** 1, 2, or 3-groove front accessory drive pulley mounted on vibration damper. Two-groove rear accessory drive pulley, mounted.
- Air Intake System:** Air intake silencer.
- Alternators:** 12 and 24 volt grounded, 24 and 32 volt insulated, with various amperage outputs. Includes built-in voltage regulator.
- By-Pass Oil Filter:** Full flow, replaceable element type, not mounted.
- Cooling System:** Keel cooling or heat exchanger with copper nickel tube bundle, mounted. Self-priming raw water pump, gear driven.
- Electrical Accessories:** Starter relay switch, low oil pressure and high water temperature alarm switches. 24 volt alarm horn.
- Engine Supports:** Marine type, 22½, 26, or 32 inch (572, 660, or 813 mm) mounting centers. Adjustable vibration isolators.
- Exhaust System:** Two 3 in. (76 mm) flanges for dry type system, mounted.
- Flywheel and Flywheel Housing:** SAE 1 and SAE 2 for use with 11.5 and 14 in. (292 and 356 mm) O.C. clutch adaptation.
- Front Power Take-Off:** Available for up to 95 bhp (71 kW).
- Instrument Panel:** Includes starting switches and gauges for water temperature, oil pressure, marine gear oil pressure; electric voltmeter, hourmeter, or tachometer, not mounted.

Available Equipment continued on back page

