

## standard equipment

**Air Box Drain Tubes**

**Air Inlet Housing**

**Air Silencer**

**Alternator**—12 volt, 42 amp, Models 1062-3000, 1062-3001, 1062-5000, and 1062-5001 only

**Crankshaft Pulley**

**Engine Mounts**—Includes mounts for engine and marine gear

**Exhaust Manifold**—Water cooled

**Flywheel Housing**—SAE #2

**Fuel Filters**

**Governor**—Variable speed, Models 1062-3000, 1062-3001, 1062-5000, 1062-5001; limiting speed, Model 1062-6001

**Heat Exchanger**

**Injectors**—Cam-operated, unit type, clean tip

**Instruments**—Includes ammeter, hourmeter, tachometer, and oil pressure gauge and water temperature gauge for engine and marine gear

**Lube Oil Cooler**

**Lube Oil Filter**—Full flow

**Marine Gear**—Allison "M" type, hydraulic reverse and reduction gear, 2 to 1 ratio

**Oil Pan**—Cast iron pan for 21°-30° inclination angle, rear sump, Models 1062-3000, 1062-3001, 1062-5000, 1062-5001; stamped steel pan for 10° inclination angle, Model 1062-6001 only


**Starting Motor**—12 volt

**Vibration Damper**

**Water Filter**—Fresh water filter with 10 gallon (37.9 Liters) capacity

For complete specifications and a listing of standard and optional equipment, consult your authorized Detroit Diesel Allison Representative.

Specifications subject to change without notice.



**Detroit Diesel Allison**

Division of General Motors Corporation

13400 West Outer Drive Detroit, Michigan 48228

In Canada: Diesel Division: General Motors of Canada Limited London Ontario

