

## standard equipment

---

**Air Cleaners**—Oil bath

**Air Inlet Housing**—Aluminum housing with manual shutdown

**Alternator**—Battery charging, 24 volt, 65 amp

**Crankshaft Pulley**—9.40 in (238.76 mm) diameter, poly-vee

**Engine Mounts**—Trunnion mounts

**Exhaust Manifold**—Water-cooled

**Flywheel Housing**—SAE #0, dual starter pads

**Flywheel**—SAE #0

**Fuel Filter and Strainer**

**Governor**—Variable speed

**Instruments**—Includes tachometer, oil pressure gauge, water temperature gauge, and drive oil pressure gauge

**Keel Cooling**

**Lube Oil Filters**—Full-flow filters, dual can

**Marine Gear**—Twin Disc MG-540, 7 to 1 ratio

**Oil Cooler**

**Oil Pan**—For 15° front or rear down operating angle, dual sump

**Starting Equipment**—dual 24 volt

**Vibration Damper**—single, heavy, viscous

For complete specifications and a listing of standard and optional equipment, consult your authorized Detroit Diesel Allison Distributor or Dealer.

---

Specifications subject to change without notice.



**Detroit Diesel Allison**

Division of General Motors Corporation

13400 West Outer Drive Detroit, Michigan 48228