


ALTERNATOR SPECIFICATIONS

Manufacturer :	Leroy Somer	<ul style="list-style-type: none"> • Leroy Somer is a branch of Emerson Electric Inc. • Compliance with NEMA MG21, UTE NF C51.111, VDE 0530, BS 4999, CSA standards. • 2/3 pitch, • Low reactance ($X^{\prime}d < 12\%$). • Vacuum-impregnated windings with epoxy varnish. IP21 drip proof • AREP type allows sustained short circuit current of up to 300% of rated current for up to 10 seconds. • Total harmonic TGH/THC < 4%
Type :	LSA50.1S4	
Pole : number	4	
Exciter type :	AREP	
Insulation : class, temperature rise	H / H	
Voltage regulator :	R448	
Bearing : number, type :	1 , Sealed	
Coupling :	Direct	
Voltage regulation 0 to 100% load :	+/-1%	
Recovery time (20% Volt dip) ms :	<1000ms	
Reactance $X^{\prime}d$, % :	15.5 %	
Heat rejection KW :	55.00 kW	
<i>Peak motor starting KVA :</i> (Maximum at 35% voltage dip)		
480V : SHUNT / With PMG	2413/ 2413	
600V :	2408	

CONTROL PANEL

Microprocessor control panel is available on all the models. Compatible with 12 or 24 Volts Engine electrical systems.



Standard features :

AC voltmeter, AC ammeter, Frequency meter,
 Engine shutdown : Oil pressure, High water temperature, Low water level, Overspeed, Overcrank.
 Engine parameters : Oil pressure, Water temperature, Fuel level, Running time meter, Battery voltage.
 Emergency Stop Button, Internal clock.
 Communication via a RS485 for remote management (software is an option)

Optional :

- NFPA 110 level 1
- Remote annunciator for NFPA 110 Level 1