

standard equipment

Air Box Drain Tubes**Air Inlet Housing****Air Silencer**

Alternator—12 volt, 42 amp, Models 1062-3000, 1062-3001, 1062-5000, and 1062-5001 only

Crankshaft Pulley

Engine Mounts—Includes mounts for engine and marine gear

Exhaust Manifold—Water cooled

Flywheel Housing—SAE #2

Fuel Filters

Governor—Variable speed, Models 1062-3000, 1062-3001, 1062-5000, 1062-5001; limiting speed, Model 1062-6001

Heat Exchanger

Injectors—Cam-operated, unit type, clean tip

Instruments—Includes ammeter, hourmeter, tachometer, and oil pressure gauge and water temperature gauge for engine and marine gear

Lube Oil Cooler

Lube Oil Filter—Full flow

Marine Gear—Allison "M" type, hydraulic reverse and reduction gear, 2 to 1 ratio

Oil Pan—Cast iron pan for 21°-30° inclination angle, rear sump, Models 1062-3000, 1062-3001, 1062-5000, 1062-5001; stamped steel pan for 10° inclination angle, Model 1062-6001 only


Starting Motor—12 volt

Vibration Damper

Water Filter—Fresh water filter with 10 gallon (37.9 Liters) capacity

For complete specifications and a listing of standard and optional equipment, consult your authorized Detroit Diesel Allison Representative.

Specifications subject to change without notice.



Detroit Diesel Allison

Division of General Motors Corporation

13400 West Outer Drive Detroit, Michigan 48228

In Canada: Diesel Division: General Motors of Canada Limited London Ontario

