


NATURAL GAS GENSET

MODEL: KS100UG

100 kW / 125 kVA Stand-by Power @ 60Hz

91 kW / 114 kVA Prime Power @ 60Hz



Standard Features:

- Electric starter, charge alternator 12V, electronic governor.
- Single bearing alternator IP21, insulation class H/H
- Radiator 50°C (122°F) max. T° air inlet with coolant cap
- Skid and vibration isolators
- Dry type air filter
- · Main line circuit breaker
- 12V battery, rack and cable
- Industrial silencer (loose)
- User manual

- We provide a full line of products with high quality recognized engines and alternators.
- Each and every unit is factory tested. All generator sets are also prototype tested.
- A one year limited warranty covers all systems and components. Two and five years extended are also available.
- Service and parts are available from our distributors as a single source of responsibility.

GENERATOR RATINGS

| Voltage 77 | Tiple Street | | | anady) alekana | Stringly Replace Committee World | |
|------------|--------------|---|-----|-------------------|----------------------------------|----------|
| 600/347V | 60 | 3 | 0.8 | 120 | 100 / 125 | 91 / 114 |
| 480/277V | 60 | 3 | 0.8 | 150 | 100 / 125 | 91 / 114 |
| 440/254V | 60 | 3 | 0.8 | 164 | 100 / 125 | 91 / 114 |
| 220/127V | 60 | 3 | 0.8 | 328 | 100 / 125 | 91 / 114 |
| 208/120V | 60 | 3 | 0.8 | 347 | 100 / 125 | 91 / 114 |

Stand-By ratings are continuous for the duration of any power outage. No overload capacity is specified at this ratings. Prime ratings are continuous per BS 5514, DIN 6271, ISO-3046 and IEC 34-1 with 10% overload capacity one hour in twelve hours.

7.660.32

