

GA-Series Generators — 2.3 to 9.7 KW — Single Phase

MODEL	GA-2.3R2	GA-2.5H	GA-3.6RZ3	GA-3.6HZ	GA-6RZ2	GA-6RZR2	GA-6HZ	GA-6HZR	GA-9.7HZ
GENERATOR									
Design	Brushless								
Maximum Output	2,300 W	2,500 W	3,600 W	3,600 W	6,000 W	6,000 W	6,000 W	6,000 W	9,700 W
Continuous Output	2,000 W	2,200 W	3,200 W	3,200 W	5,000 W	5,000 W	5,000 W	5,000 W	8,400 W
Voltage	120	120	120/240	120/240	120/240	120/240	120/240	120/240	120/240
Frequency/Phase	60 Hz / Single Phase								
Voltmeter	Standard								
Full Power Switch	—	—	Standard						
Main Circuit Breaker	17A (1-pole)	20A (1-pole)	13.5A (2-pole)	13.5A (2-pole)	21A (2-pole)	21A (2-pole)	21A (2-pole)	21A (2-pole)	35A (2-pole)
Sound Level dB(A) Full load 23 feet	73	70	77	73	81	81	74	74	88
GASOLINE ENGINE									
Make/Model	Robin EH-17-2	Honda GX-160	Robin EH-25-2	Honda GX-240	Robin EH-34	Robin EH-34	Honda GX-340	Honda GX-340	Honda GX-610
Starting System	Recoil	Recoil	Recoil	Recoil	Recoil/Electric	Recoil	Recoil/Electric	Recoil	Recoil/Electric
HP (kw)	6.0 (4.2)	5.5 (4.1)	8.5 (6.4)	8.0 (6.0)	11.0 (8.25)	11.0 (8.25)	11.0 (8.25)	11.0 (8.25)	18.0 (13.5)
Rated Speed - RPM	3600								
Low Oil Shutdown	Standard								
Fuel Gauge	Standard								
Automatic Idle Control	N/A	N/A	Standard						
Fuel Tank Capacity gal (liters)	3.6 (13.6)	3.6 (13.6)	3.6 (13.6)	5.0 (18.9)	5.0 (18.9)	5.0 (18.9)	5.0 (18.9)	5.0 (18.9)	10 (37.9)
Running Time @ full load hours/tank	7.25	7.0	5.0	7.5	5.5	5.5	5.5	5.5	6.75
SIZE									
Length in. (cm)	20.75 (53)	19.75 (50)	24 (61)	25 (63)	24.75 (63)	24.75 (63)	30.5 (77)	25.75 (65)	31.25 (79)
Height in. (cm)	20.5 (52)	18.25 (46)	21.75 (55)	18.75 (47)	24.75 (63)	24.75 (63)	19 (48)	19 (48)	28 (71)
Width in. (cm)	15.75 (40)	16.25 (41)	18.75 (47)	19.75 (50)	18.75 (48)	18.75 (48)	20.25 (51)	20.25 (51)	21.25 (54)
Dry Wt. lb. (kg)	101 (46)	107 (49)	150 (68)	165 (75)	179 (81)	189 (86)	202 (92)	188 (85)	329 (149)
AMPS									
Max./Cont. 120V	19.2/16.6	20.8/18.3	30/26.6	30/26.6	50/41.6	50/41.6	50/41.6	50/41.6	80.8/70
Max./Cont. 240V	—	—	15/13.3	15/13.3	25/20.8	25/20.8	25/20.8	25/20.8	40.4/35