


ALTERNATOR SPECIFICATIONS

Manufacturer :	Leroy Somer	<ul style="list-style-type: none"> • Leroy-Somer is a branch of Emerson Electric Inc. • Compliance with NEMA MG21, UTE NF C51.111, VDE 0530, BS 4999, CSA standards. • 2/3 pitch, 12 leads reconnectable. • Low reactance ($X^d < 12\%$). • Vacuum-impregnated windings with epoxy varnish. IP21 drip proof • Generator allows as standard sustained short circuit current of up to 300% of rated current for up to 10 seconds.
Type :	LSA461L8	
Pole : number	4	
Exciter type :	AREP	
Insulation : class, temperature rise	H / H	
Voltage regulator :	R448	
Bearing : number, type :	1, Sealed	
Coupling :	Direct	
Voltage regulation 0 to 100% load :	+/- 1%	
Recovery time (20% Volt dip) ms :	< 500 ms	
Reactance X^d , % :	9.1 %	
Heat rejection KW :	17.90 kW	
Peak motor starting KVA: (Maximum at 35% voltage dip)		
480V : SHUNT / With PMG	900/ 900	
600V :	834	

CONTROL PANEL

Microprocessor control panel is available on all the models. Compatible with 12 or 24 Volts Engine electrical systems.

	<p>Standard features :</p> <p>AC voltmeter, AC ammeter, Frequency meter, Engine shutdown : Oil pressure, High water temperature, Low water level, Overspeed, Overcrank. Engine parameters : Oil pressure, Water temperature, Fuel level, Running time meter, Battery voltage. Emergency Stop Button, Internal clock. Communication via a RS485 for remote management (software is an option)</p>
--	--

Optional :

- NFPA 110 level 1
- Remote annunciator for NFPA 110 Level 1